

## F598 Heavy Duty Spray Adhesive

A versatile **all-round** spray adhesive ideal for bonding an **extensive range** of materials and **floorcoverings**.

- **High Adhesive Content**
- **Uniform Spray Pattern**
- **Long Open Time**
- **Easy to Use**
- **Fast Drying**

### Description:

F598 is a multipurpose spray adhesive suitable for bonding a wide variety of materials giving a rapid and strong bonding formation and is economical in use.

### Uses:

F598 bonds a wide variety of substrates including carpets, wood, concrete, stone, tiles, rubber, foam, metals, rigid plastics, polyethylene, canvas fabrics, cardboard, paper and cork.

F598 is not suitable for expanded polystyrene, highly plasticised Vinyl or PVC floorcoverings.

### Sub-Floors:

F598 is suitable for bonding to Concrete bases, cement screed, anhydrite screed, smoothing & levelling underlayment, flooring grade chipboard, hardboard, plywood, stone, terrazzo, quarry tiles, ceramic, brickwork and plaster.

It is also suitable for bonding to metal, glass and most plastics.

### Specification:

Adhesive type:	SBR Adhesive
Colour:	Amber
Flashpoint:	Highly-Flammable.
Coverage:	Approximately 2.5m <sup>2</sup> per can.
Application Temperature:	+5°C – +25°C.
Working Time:	Approximately 10 Minutes depending on temperature, humidity & subfloor.
Storage & Shelf Life:	12 months in original, unopened can between +15°C and +35°C. Store cans in accordance with the requirements of the Petroleum Regulations.
Container sizes:	500ml Can.



### Directions for Use:

#### IMPORTANT

Before using F598 Spray Adhesive please refer to the safety guide and data sheet available at [www.floorwise.co.uk](http://www.floorwise.co.uk)

All phases of the installation should comply with the latest editions of the following standards:

- BS 8102 Code of Practice for the protection of buildings against water from the ground.
- BS 5325 Code of Practice for the installation of textile floorcoverings.
- BS 8203 Code of Practice for the installation of resilient floorcoverings.

### Preparation:

Surfaces to be bonded should be clean, dry and free from dust.

Shake can well before use.

### Application:

Spray an even coat of adhesive onto both surfaces.

Allow adhesive to become touch dry, so that it does not transfer to finger, which can be almost immediately.

Press the floorcovering firmly into place which will bond immediately.

Allow approximately 10 minutes for the adhesive to set.

After use invert the can and press the nozzle to clear adhesive from the spray tip.

### Cleaning:

Remove any overspray immediately with Floorwise solvent cleaner or the minimum of white spirit.

### Safety Guidance:

<b>F598 SPRAY ADHESIVE</b>		<b>UN1950</b>
Contains DICHLOROMETHANE, Hydrocarbons, C6-C7, N-Alkanes, Isoalkanes, Cyclics, <5% N-Hexane		
<b>DANGER</b>   	<p>Extremely flammable aerosol.            Pressurised container: may burst if heated.            Causes skin irritation.            Causes serious eye irritation.            May cause drowsiness or dizziness.            Suspected of causing cancer.            Harmful to aquatic life with long lasting effects.</p> <p>Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.            Do not spray on an open flame or other ignition source.            Do not pierce or burn, even after use.            Avoid breathing spray.            Use only outdoors or in a well-ventilated area.            Wear protective gloves/ protective clothing/ eye protection/ face protection.            Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.            Dispose of contents/ container in accordance with national regulations.</p> <p>A full safety data sheet relating to this product is available at <a href="http://www.floorwise.co.uk">www.floorwise.co.uk</a></p>	
	<b>500 ml</b> <span style="border: 1px solid black; padding: 2px;">650</span> e 3 <b>UK CA</b>	



A full materials safety data sheet relating to this product is available at [www.floorwise.co.uk](http://www.floorwise.co.uk)

This product data sheet is provided for guidance only. For further information and advice on application, or if in any doubt as to the suitability of the product for the installation, please contact our Technical Department for advice.